



Auto Flasher WM FL016

L×W×H(mm): 30.5×30.5×30



Features

- Failure indication;
- High sensitive and stable electronic timing;
- Suitable for flasher light during car turning;
- Wide operating voltage, temperature range and long life;
- Standard terminals, usage and Replacement easily.

Ordering Information 订货说明

WM FL016	- 12	- F	656	S
1	2	3	4	5
1 Part number 型号: FL016 F016M: METAL COVER	2 Coil rated Voltage(VDC)线圈额定电压: 12: 12V; 24: 24V	3 Failure indication 缺灯故障报警: BJ:Failure indication; F: No Failure indication	4. 656: 内置继电器用 656, NIL: STANDARD	5. S: Sealed version; NIL:Dust proof

Technical Characteristics 性能参数

Rated Voltage 额定电压	12VDC, 24VDC
Operating Voltage 工作电压	11VDC ~ 15VDC, 22VDC ~ 30VDC
Test Voltage 试验电压	13VDC ± 0.2VDC, 26VDC ± 0.4VDC
Test Temperature 试验温度	20°C±2°C
Switch Power 切换负载	21W ~ 150W
Bulb failure warning 缺灯提醒	>140 times per minute
Flashing Frequency 闪光频率	60 ~ 120 times per minute
Duty Ratio 占空比	30% ~ 70%
Operating Temperature 环境温度	-40°C ~ +80°C
Life 寿命	400 working hours
Weight 重量(Approx.)	25g

Layout (Bottom views, Unit: mm)外形尺寸、接线图（底视图）

Dimensions 外形尺寸	Wiring diagram(Bottom views) 接线图