

Auto LED Flasher WM FLL050

L×W×H(mm): 28×28×25(+16)



Features

- Suitable for flasher light during car turning;
- High sensitive and stable electronic timing;
- Wide operating voltage, temperature range and long life;
- Standard terminals, usage and Replacement easily;
- Without ticking sound.

Ordering Information 订货说明

<u>WM FLL050</u> - <u>12</u> 1 2	
1 Part number 型号: WM FLL050	2 Coil rated Voltage(VDC)线圈额定电压: 12: 12V; 24: 24V

Technical Characteristics 性能参数

Rated Voltage 额定电压	12VDC, 24VDC
Operating Voltage 工作电压	11VDC ~ 15VDC, 22VDC ~ 30VDC
Test Voltage 试验电压	13VDC ± 0.2VDC, 26VDC ± 0.4VDC
Test Temperature 试验温度	20°C ± 2°C
Switch Load 切换负载	0.1W ~ 100W (0.02A ~ 10A)
Max Power 最大负载	100W
Flashing Frequency 闪光频率	60 ~ 120 times per minute
Duty Ratio 占空比	30% ~ 70%
Operating Temperature 环境温度	-40°C ~ +80°C
Life 寿命	400 working hours
Weight 重量(Approx.)	32g

Layout (Bottom views, Unit: mm)外形尺寸、接线图 (底视图)

Dimensions 外形尺寸	Wiring diagram(Bottom views) 接线图
28 28 16 10 5.5 25 130 32 6.3 Red wire Black wire WM FLL050 Flasher for LED 12V 0.05A-10A +: Red wire L: Black wire	+12VDC + L T/S SW Pilot LED Pilot