

Auto LED Flasher **WM FLL302**

L×W×H(mm): 30.5×30.5×30

**Features**

- Suitable for flasher light during car turning;
- High sensitive and stable electronic timing;
- Wide operating voltage, temperature range and long life;
- Standard terminals, usage and Replacement easily;
- With ticking sound.

Ordering Information 订货说明

WM FLL302	- 12	- KT
1	2	3
1 Part number 型号: WM FLL302		3 Flashing Frequency 闪光频率: KT: adjustable 可调;
2 Coil rated Voltage(VDC)线圈额定电压: 12; 12V; 24; 24V		Nil: Non-adjustable 不可调

Technical Characteristics 性能参数

Rated Voltage 额定电压	12VDC, 24VDC
Operating Voltage 工作电压	11VDC ~ 15VDC, 22VDC ~ 30VDC
Test Voltage 试验电压	13VDC ± 0.2VDC, 26VDC ± 0.4VDC
Test Temperature 试验温度	20°C ± 2°C
Switch Load 切换负载	0.1W ~ 150W (0.02A ~ 20A)
Max Power 最大负载	150W
Flashing Frequency 闪光频率	60 ~ 120 times per minute
Duty Ratio 占空比	30% ~ 70%
Operating Temperature 环境温度	-40°C ~ +80°C
Life 寿命	400 working hours
Weight 重量(Approx.)	25g

Layout (Bottom views, Unit: mm)外形尺寸、接线图（底视图）

Dimensions 外形尺寸	Wiring diagram(Bottom views) 接线图